

BEIJING HUATENG HIGHTECH CO LTD

123 N ZHONGGUANCUN ST, HAIDIAN DIST, BEIJING 100084 CN

301-G30(F)(r1)

Polybutylene Terephthalate (PBT), glass reinforced, "KAIFA", furnished as pellets

Color	Min Thk (mm)	Flame Class	Flame		RTI	RTI	RTI
			HWI	HAI	Elec	Imp	Str
ALL	0.8-0.88	V-0	3	0	75	75	75
	3.0	-	-	-	75	75	75

Comparative Tracking Index (CTI): -

Dimensional Stability (%): -

High-Voltage Arc Tracking Rate (HVTR): -

High Volt, Low Current Arc Resis (D495): -

Dielectric Strength (kV/mm): -

Volume Resistivity (10xohm-cm): -

r1 - Virgin and Regrind up to 50% have the same basic material characteristics with regard to flammability characteristics in 0.8mm thickness for black color, tensile strength, and softening temperature only.

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

Report Date: 1985-10-14

Last Revised: 2006-10-10

Underwriters Laboratories Inc®

